


	RioTouch Technology Co., Ltd	
	Room 205, No. 393, Chang'an Section, Tai'an Road, Chang'an Town, Dongguan City, Guangdong Province	
	Web: www.RioTouch.com	
Touch table with lifting and lowering		
Model		U+43
Product picture		
Display specification		
Diagonal display size		43(inch)
Panel type	DLED	√
Active area (mm)		941.184(H) * 529.416(V)
Resolution	3840*2160 /60hz	√
Hardness Glass	Mohs-7 level	√
Glass Panel	Anti-Glare glass with zero bonding	√
Aspect Ratio	16:9	√
Contrast Ratio	1200:1 (type)	√
Brightness	300cd/m2	√
Viewing angle	89/89/89/89 (Typ.)(CR≥10)	√
Lifespan	50,000 hours	√
Touch Type		
Touch technology	capacitive touch	√
Multi touch	Max 10 points(Windows)	√
Touch Precision	1 mm (over 90% Area)	√
Auto-calibrate	Yes	√
Anti-light	Yes	√
Minimum object size	1mm	√
Touch Response Time	First Point <2 ms, Continuation <8 ms	√
Sound		
Speakers	2	√
Speakers	5W*2	√
Total Power Amplifiers	≦10w	√
Bottom Side Connections		
HDMI IN	1	√
HDMI OUT	1	√
TYPE-C	2	√
USB 3.0	2	√
RJ45 IN	1	√
LINE IN	1	√
Earphone	1	√
Riotouch Central		
Android Version	Android 12.0	√
Chip	RK3588	√

CPU	Cortex-A76+Cortex-A55 2.4GHz	√
GPU	Mali-G610 MC4	√
Memory	4G (8G optional)	√
Storage	32G (128G optional)	√
Over-the-Air Updates (OTA)	YES	√
Bluetooth version	5.0	√
WiFi Standard	WIFI6	√
General Information		
Power Supply	~ 100-240 V (50/60Hz)	√
Switch On / Off	Yes	√
Standby Energy Consumption	≤ 0.7 Watt	√
Power Consumption		Maximun< 80W Eco<25W
Screen Dimensions	(WxDxH)	981.7 * 575.6 * 30mm
Dimensions Package	(WxDxH)	1075 * 690 * 160mm
Warranty	ONE year for the whole product . (can be extended, it's for an option)	√
Environmental conditions		
Operating Temperature	0°C - 38°C/32 - 100 F	√
Storage Temperature	-20°C - 60°C/-4 - 140 F	√
Storage Humidity	10 % - 90 %	√
Usage Humidity	10 % - 90 %	√
Accessories		
Accessories	Remote control *1pcs, 1.5m power cord *1pcs, aerial rod*3pcs	