


Vertical advertising machine

Model		AD43	AD55	AD65
Product Images				
				
Display Specifications				
Screen diagonal size		43 (inch)	55 (inch)	65 (inch)
Screen type	DLED	√	√	√
Screen size (mm)		941.184 * 529.416	1209.6 * 680.4	1428.48 * 803.52
resolution	3840*2160	√	√	√
Pixel pitch (mm)		0.2451 * 0.2451	0.315 * 0.315	0.372 * 0.372
Hardness of tempered glass	Mohs hardness7class	√	√	√
Glass type	tempered glass	√	√	√
Aspect Ratio	16:9	√	√	√
Contrast	1200:1 (type)	√	√	√
Screen brightness	200cd/m2	√	√	√
Viewing angle	89/89/89/89 (Typ.)(CR≥10)	√	√	√
Theoretical service life	50,000Hour	√	√	√
Touch specifications				
Touch technology	Capacitive touch/infrared touch (optional)	√	√	√
Multi-touch	10point	√	√	√
Touch accuracy	1 mm	√	√	√
Automatic calibration	yes	√	√	√
Minimum recognition point diameter	2mm	√	√	√
Response time	Greater than2msLess than8ms	√	√	√
Speaker specifications				
speaker	2	√	√	√
Speaker power	5W*2	√	√	√
Total power	≅10w	√	√	√
Interface Specifications				
USB 3.0	1	√	√	√
USB 2.0	1	√	√	√
RJ45 IN(100M)	1	√	√	√
TF	1	√	√	√
Audio (IN/OUT)	1	√	√	√
Motherboard configuration				
System version	Android 13.0	√	√	√
chip	A527M	√	√	√
CPU	Cortex-A55, 1.8GHz	√	√	√
GPU	Mali-G57 MC01	√	√	√
Memory	2G (4G0ptional)	√	√	√
harddisk	16G (32G/64G/128G0ptional)	√	√	√
Remote upgrade	yes	√	√	√
Bluetooth version	4.2	√	√	√
WiFiVersion	WiFi5	√	√	√
Overall parameters				
power supply voltage	~ 100-240 V (50/60Hz)	√	√	√
Switch	yes	√	√	√
standby power consumption	≤ 0.5Vats	√	√	√
Overall power consumption		Maximum power < 80W Eco < 25W	Maximum power < 100W Eco < 25W	Maximum power < 120W Eco < 25W
Overall dimensions (mm)	long *Width * high	1750 * 582 * 75	1850 * 746 * 95	1950 * 877 * 95
Packaging size (mm)	Length * Width * Height	1840 * 695 * 180	1940 * 845 * 180	2140 * 970 * 180
Warranty	The product comes with a one-year warranty. (Extension is available as an optional service.)	√	√	√
Environmental conditions				
Operating temperature	0°C - 38°C / 32 - 100 F	√	√	√
Storage temperature	-20°C to 60°C / -4°C to 140°C	√	√	√
Operating humidity	10% - 90%	√	√	√
Storage humidity	10% - 90%	√	√	√
appendix				
Accessories	Power cord (1.5meters), antenna rod (1Root), remote control (1 piece)			