

IR Touch Interactive Flat Panel Display

Brand	RIOTOUCH	
Model	LTKC86RK3588	
Product picture	08:16 M Marine, April Mari	8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	Display specification	
Diagonal display size	p	86(inch)
Bezel color	Aluminum frame(White color)	V
Panel type	Ultra HD Direct type LED	V
Active area (mm)		1895.04 * 1065.96(V)
Resolution	4K UHD (3840*2160 /60hz)	V
Pixel Pitch		0.4935 mm x 0.4935 mm
Hardness Glass	Mohs-9 level - thickness ≥3.2 mm	√
Glass Panel	Anti-Glare glass with zero bonding;anti-reflective and anti-fingerprint tempered glass	V
Aspect Ratio	16:9	V
Contrast Ratio	1200:1 (type)	V
Dynamic Contrast Ratio	4000:1	√
Brightness	more than 400cd/m2	√ /
Color depth	1.07 billion colors	√ -/
Viewing angle Lifespan	50,000 hours	√ √
Lifespan	Touch Type	V
Touch Technology	IR touch	√ √
Multi Touch	Max 40 points(Windows&Android)	, √
Multi Writing	Max 20 points(Windows&Android)	, √
Touch Precision	1 mm (over 90% Area)	V
Auto-Calibration	Yes	V
Anti-light	Yes	V
Minimum object size	2mm	V
Touch Response Time	First Point <2 ms, Continuation <8 ms	√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√
Front Speakers	Sound 15W*2 (20W*2)	√
Subwoofer	20W*1	√ √
Total Power Amplifiers	20w*1 ≤60w	√ √
	Microphone (option)	
Туре	Wide-area microphones	√
Number of Microphones	8	V
Range	≥5m range, with noise reduction	V
Auto switch (Windows/Central)	Yes	√
Disconnectable	Yes	V
	Build-in camera	
Resolution	8K - 7680x4320	√
Viewing angle Capture distance	122° diagonal / 105° horizontal / 88° vertical up to 10 m	√ 2/
Capture distance Capture speed	up to 10 m 5 fps	√ √
Compatibility	Fully compatible with Android EDLA and AI features	√ √
Location	Integrated into the top frame of the display, no additional mounting required	V
	Front Side Connections	
Front Ports	Type-C * 1 line; HDMI IN * 1 line; USB3.0*2;USI	
Front Keys NFC	Power on/off; Signal source; Setting; ECO; Menu;	volume down;
Fingerprint	√ √	
ringo print	Bottom Side Connections	
RJ45 OUT	1	√ √
	<u> </u>	1 .

DIAS IN		
RJ45_IN	1	$\sqrt{}$
SPDIF OUT	1	V
MIC IN	1	V
Earphone	1	V
HDMI OUT	1	, √
TYPE C OUT	1	, √
VGA AUDIO IN		
	1	√
VGA	1	V
RS232	1	$\sqrt{}$
	Side Connection	
HDMI IN 3	1	V
Touch USB 3	1	V
HDMI IN 2	1	V
Touch USB 2	1	, √
HDMI IN 1	1	√ √
_		
Touch USB_1	1	√
DP	1	V
TYPE_C IN	1	$\sqrt{}$
Android USB 3.0	1	V
Full Source Sharing		1
USB3.0	2	$\sqrt{}$
TE CARD	1	√
II CARD		V
	IEEE 802.11a/b/g/n/ac/ax with 2	,
WIFI	x2 MIMo (hotspotonly)	$\sqrt{}$
	(both 2.4 and 5 GHz bands) (wifi6)	,
Windows OPS Slot	80-pins OPS slot	$\sqrt{}$
Bluetooth version	5.2	V
	Riotouch Central	
Android Version	Android 13.0 with EDLA	V
Chip	Rockchip RK3588	1
Сшр	¥	٧
CPU	quad-core Cortex-A76 and quad-core Cortex-A55,	$\sqrt{}$
	up to 2.4GHz	·
GPU	Mali-G610 MC4	V
NPU	6T	$\sqrt{}$
RAM	32GB DDR4	V
Flash	256GB	V
Compliant with	Windows; Mac; Linux; Android; Chrome OS	V
	Windows, Mac, Emax, Findroid, Chrome OB	,
Over-the-Air Updates	YES	$\sqrt{}$
(OTA)		· ·
(OTA) Light Sensor	YES	V
(OTA)		· ·
(OTA) Light Sensor NFC Reader/Writer	YES	V
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity	YES YES	\ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one	YES	V
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor	YES YES YES	\ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one	YES YES YES YES	\ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module	YES YES YES YES General Information	\ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply	YES YES YES YES YES General Information 100-240 V (50/60Hz)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module	YES YES YES YES General Information	\ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply	YES YES YES YES General Information 100-240 V (50/60Hz) Yes	\ \ \ \ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy	YES YES YES YES YES General Information 100-240 V (50/60Hz)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption	YES YES YES YES General Information 100-240 V (50/60Hz) Yes	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy	YES YES YES YES General Information 100-240 V (50/60Hz) Yes	√ √ √ √ √ Maximun<350W
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption	YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt	√ √ √ √ √ √ √ Maximun< 350W Eco<75W
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight	YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2)	√ √ √ √ √ √ √ √ √ Maximun< 350W Eco<75W 70
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption	YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt	√ √ √ √ √ √ √ √ √ Maximun< 350W Eco<75W 70 85
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight	YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (WxDxH)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (WxDxH)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (WxDxH) (WxDxH) (mm)	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications	YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (WxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star	√ √ √ √ √ √ √ Maximun<350W Eco<75W 70 85 1943.4*97.5*1166 mm 2090 *190 * 1307 mm 800*600 mm √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (WxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (wxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty Operating Temperature	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions 0°C - 40°C/32 - 100 °F	√ √ √ √ √ √ √ Maximun<350W Eco<75W 70 85 1943.4*97.5*1166 mm 2090 *190 * 1307 mm 800*600 mm √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty Operating Temperature Storage Temperature	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (wxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty Operating Temperature Storage Temperature	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions 0°C - 40°C/32 - 100 °F	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty Operating Temperature Storage Temperature Storage Humidity	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (KG±2) (WxDxH) (wxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions 0°C - 40°C/32 - 100 °F -20°C - 60°C/-4 - 140 °F 10 % - 90 %	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √
(OTA) Light Sensor NFC Reader/Writer Temperature, humidity and air quality three-in-one sensor Fingerprint module Power Supply Switch On / Off Standby Energy Consumption Power Consumption Net Weight Gross Weight Screen Dimensions Dimensions Package VESA Standard Certifications Warranty Operating Temperature Storage Temperature	YES YES YES YES YES YES General Information 100-240 V (50/60Hz) Yes ≤ 0.5 Watt (KG±2) (KG±2) (WxDxH) (wxDxH) (mm) CE: EMC + LVD / RoHS / FCC/CCC / Energy Star THREE years Environmental conditions 0°C - 40°C/32 - 100 °F -20°C - 60°C/-4 - 140 °F	√ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √

Accessories

WIFI antenna*2pcs; No ink Active pen * 2pcs (precise and distinct writing), Remote control *1pcs, 3m power cord *1pcs, 3m HDMI cable *1pcs, 3m USB touch cable *1pcs; 3m VGA and 3m Type-C cable wall mount kit; Mobilestand (800mm*600mm, Bearing: 180kg)

Smart features

- * Screen recording up to 4K
- * Simultaneous presentation on multiple devices
- * AI tools: drawing, searching, generating quizzes
- * Linking with Google accounts, integration with Chrome and YouTube
 - * Remote management software: update, lock, install apps, etc.
 - * Free perpetual license
 - * Cloud usage statistics, no local installation
 - * Wireless transmission (casting) between screens Eshare
 - *Perpetual license

Cloud

*Offers the option to personalize each user and securely access your accounts and files in the cloud.

*Allow secure and accessible cloud storage (Google Drive, OneDrive.) to be linked to download documents and multimedia files, optimizing accessibility and collaboration.

Wireless transmission

*It allows for wireless connection of various devices without the need for additional hardware, facilitating projection and collaboration on the interactive display. Connect via Eshare software.

*Wireless connection of a Windows or Mac device that will allow you to use it wirelessly and tactilely