




Dong Guan RioTouch Technology Co., Ltd

Room 205, No. 393, Chang'an Section, Tai'an Road, Chang'an Town, Dongguan City, Guangdong Province

Web: www.RioTouch.com

IR Touch Interactive Flat Panel Display

Model		LTKC65V100	LTKC75V100	LTKC86V100
Product picture				
Display specification				
Diagonal display size		65(inch)	75(inch)	86(inch)
Bezel color	Aluminum frame(White color)	√	√	√
Panel type	Ultra HD Direct type LED	√	√	√
Active area (mm)		1428.48 (H) * 803.52 (V)	1649.66(H) * 927.93(V)	1895.04 (H) * 1065.96(V)
Resolution	3840*2160 /60hz	√	√	√
Pixel Pitch		0.372mm x 0.372mm	0.429 mm x 0.429 mm	0.4955 mm x 0.4955 mm
Hardness Glass	Mohs-7 level	√	√	√
Glass Panel	Anti-Glare glass with zero bonding	√	√	√
Aspect Ratio	16:9	√	√	√
Contrast Ratio	1200:1 (type)	√	√	√
Brightness	400cd/m2	√	√	√
Color depth	1.07 billion colors	√	√	√
Viewing angle	178°	√	√	√
Lifespan	50,000 hours	√	√	√
Touch Type				
Touch Technology	IR touch	√	√	√
Multi Touch	Max 40 points(Windows)	√	√	√
Multi Writing	Max 20 points(Android)	√	√	√
Touch Precision	1 mm (over 90% Area)	√	√	√
Auto-Calibration	Yes	√	√	√
Anti-light	Yes	√	√	√
Minimum object size	2mm	√	√	√
Touch Response Time	First Point <2 ms, Continuation <8 ms	√	√	√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√	√	√
Sound				
Front Speakers	15W*2 (20W*2) Optional	√	√	√
Subwoofer	20W*1	√	√	√
Total Power Amplifiers	≅ 60w	√	√	√
Microphone (option)				
Type	Wide-area microphones	√	√	√
Number of Microphones	8	√	√	√
Auto switch (Windows/Central)	Yes	√	√	√
Disconnectable	Yes	√	√	√
camera (option)				
Number of images	4800M (AI) /6400M	√	√	√
Number of images	1300MP	√	√	√
Maximum resolution and frame rate	4208*3120(30fps)	√	√	√
FOV(field of view)	120 °	√	√	√
Front Side Connections				
Front Ports	Type-C * 1 line; HDMI IN * 1 line; USB3.0*3; USB-B*1			
Front Keys	Power on/off; Signal source; Setting; ECO; Menu; Volume down; Volume up			
NFC	√			
Bottom Side Connections				

RJ45 IN	1	√	√	√
HDMI OUT	1	√	√	√
SPDIF OUT	1	√	√	√
Earphone	1	√	√	√
Side Connection				
Touch USB (HDMI1&HDMI2)	1	√	√	√
HDMI IN 1	1	√	√	√
HDMI IN 2	1	√	√	√
Android USB 3.0	1	√	√	√
Android USB 2.0	1	√	√	√
TF CARD	1	√	√	√
RS232	1	√	√	√
WIFI	Wi-Fi 5(2.4G+5G)	√	√	√
Windows OPS Slot	80-pins OPS slot	√	√	√
Bluetooth version	5.1	√	√	√
Riotouch Central				
Android Version	Android 14.0	√	√	√
Chip	GK6780V100	√	√	√
CPU	8 core ARM Cortex-A55,1.5GHZ	√	√	√
GPU	Mali-G52 MC2	√	√	√
RAM	4G, 8GB, 16GB DDR	√	√	√
Memory	32GB, 64GB, 128GB EMMC	√	√	√
Compliant with	Windows; Mac; Linux; Chrome OS	√	√	√
Over-the-Air Updates (OTA)	YES	√	√	√
Light Sensor	YES	√	√	√
NFC Reader/Writer	YES	√	√	√
General Information				
Power Supply	100-240 V (50/60Hz)	√	√	√
Switch On / Off	Yes	√	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√	√
Power Consumption		Maximun< 290W Eco<75W	Maximun< 320W Eco<75W	Maximun< 350W Eco<75W
Net Weight	(KG±2)	45	55	70
Gross Weight	(KG±2)	55	68	85
Screen Dimensions	(WxDxH)	1470.9 *97.5* 897.5 mm	1692.1 *97.5*1021.9 mm	1943.4*97.5*1166 mm
Dimensions Package	(WxDxH)	1622 * 190 * 1038 mm	1842 * 190 * 1163 mm	2090 *190 * 1307 mm
VESA Standard	(mm)	600*400 mm	600*400 mm	800*600 mm
Certifications	CE: EMC + LVD / RoHS / FCC/CCC	√	√	√
Warranty	ONE year for the whole product and THREE years for touch parts by default. (can be extended, it's for an option)	√	√	√
Environmental conditions				
Operating Temperature	0°C - 40°C/32 - 100 °F	√	√	√
Storage Temperature	-20°C - 60°C/-4 - 140 °F	√	√	√
Storage Humidity	10 % - 90 %	√	√	√
Usage Humidity	10 % - 90 %	√	√	√
Accessories				
Accessories	WIFI antenna*2pcs; No ink pen * 2pcs, Remote control *1pcs, 1.5m power cord *1pcs, 1.5m HDMI cable *1pcs, 1.5m USB touch cable *1pcs; wall mount kit			