




High-Performance, meet Interaction

RK3588 interactive screen – Innovating learning and collaboration, redefining technology for education and business





Best Performance Interactive Screen For Education And Business
















Experience the power of an intuitive app-based user interface that makes teamwork a breeze. Whether in the classroom or the boardroom, our robust whiteboard functionality allows for real-time sharing and brainstorming, taking your productivity to new heights.



Naturally Smooth Writing with Digital Accuracy

Write, annotate, and collaborate during presentations with a pen-on-paper feel. With dual-pen recognition to support group collaboration, and Ultra Fine Touch technology and 3mm tipped pens for lag-free digital precision, offers unparalleled writing accuracy with a natural flow.







Touch

Up to 40 points of touch





8K Resolution With Immense Picture Quality

A dynamic display range has 8k video resolution with an unparalleled visual experience offer true to life color and picture quality, enhances any classroom or meeting room experience and adds life to it.





Zero Bonding

Zero boning technology ensures high precision touch and dust free clarity screens.













8Array Microphones with speaker tracking

8 microphones and speaker-tracking technology locate the sound source in real-time, ensuring the speaker is always the center of attention.





48MP Al Camera Auto framing

With auto-framing, the Riotouch display automatically adjusts to achieve the best angle based on the number of participants and their location, so it feels like a face-to-face interaction.













Multiple Ports





802.11ax.



- Finger Print Module
- Light Sensor
- PM2.5 Sensor



Type-C Versatile Connectivity

Experience seamless connectivity with the versatile Type-C port.

Effortlessly connect to webcams, microphones, speakers, USB flash drives, and wired networks by simply plugging in a cable. And with up to 100W of charging performance, your device stays poweredthroughout your lessons.





Transform Images into Actionable Insights




From Image to Insight

"Capture. Convert. Conquer."

"With RK3588, capturing an image is just the beginning. Convert it into text and conquer the information it holds. Whether it's documents. receipts,or notes, RK3588's OCR turns images into insights at your fingertips."







Object handling




Google search



Transform Your Writing with Umind Advanced Al Pen


Al-powered pen tools, integrated into our Umind whiteboard software, offer unparalleled accuracy and intuitive functionality.






Ignite Learning with RK3588 – Where Every Subject Shines

PhET Interactive Simulations – Your gateway to a world of science and math, now powered by RK3588.















Empowering Education, Amplifying Insights

- Your gateway to a world of science and math








From primary to higher education, our platform, covers a wide range of subjects, igniting curiosity and fostering deep understanding. Customize your curriculum, create dynamic content, and contribute to a learning revolution that transforms teaching and empowers learners to achieve more."





RK3588: The Core of Your 3D Vision Transform Ideas into Reality



Natural Sciences

Anatomy and Physiology Geography and Earth Sciences Chemistry and Molecular Structure Biology and Ecology Astronomy and Space Science Physics and Mechanics







DMS-"Simplify, Streamline, Secure."



Secure your documents, smarten your management, and enjoy a seamless experience, all in one unified platform."










"Experience cloud sync like never before. Our service harmonizes with Google,OneDrive, and more, uniting all your data in perfect sync."

Secure, Smart, and Social Cloud



"Secure your data, smarten your access, and socialize your cloud experience. Our service supports Google, OneDrive, and more for a truly social cloud."





Multiple user login



Beyond the Drive, Into the Cloud


- Step beyond the drive and into the cloud with our service.
- Multi-user functionality meets Google, OneDrive, and other cloud giants.



The Power of Now, In Every Update

Feel the power of now with every **OTA** update.

Immediate,impactful,and always improving.





Beyond the Cloud Into the Ecosystem

Take your EDLA experience beyond the cloud and into the rich ecosystem of Google services.





• IR Touch Interactive Flat Panel Display-RK3588

Model		LT65RK3588	LT75RK3588	LT86RK3588	LT98RK3588	LT105RK3588	
Diagonal display size		65(inch)	75(inch)	86(inch)	98(inch)	105(inch)	
Bezel color	Aluminum frame(White color)	√	√	√	√	√	
Panel type	Ultra HD Direct type LED	√	√	√	√	√	
Active area (mm)		1428.48 (H) * 803.52 (V)	1649.66 * 927.93(V)	1895.04 * 1065.96(V)	2187.8(H)×1242.8(V)mm	2487.4(H) × 1070.6(V)mm	
Resolution	3840*2160 /60hz	√	√	√	√	5120*2160 /60hz	
Pixel Pitch		0.372mm x 0.372mm	0.429 mm x 0.429 mm	0.4935 mm x 0.4935 mm	0.5622×0.5622 mm	0.4785×0.4785	
Hardness Glass	Mohs-7 level	√	√	√	√	√	
Glass Panel	Anti-Glare glass with zero bonding	√	√	√	√	√	
Aspect Ratio	16:9	√	√	√	√	21:9	
Contrast Ratio	1200:1 (type)	√	√	√	√	4000:1 (type)	
Dynamic Contrast Ratio	4000:1	√	√	√	9500:1	14000:1	
Brightness	General: 350cd/m2 Peak 500cd/m2	√	√	√	480cd/m2	480cd/m2	
Color depth	1.07 billion colors	√	√	√	√	√	
Viewing angle	178°	√	√	√	√	√	
Lifespan	50,000 hours	√	√	√	√	√	
	Touch Type						
Touch Technology	IR touch	√	√	√	√	√	
Multi Touch	Max 40 points(Windows)	√	√	√	√	√	
Multi Writing	Max 20 points(Windows)	√	√	√	√	√	
Touch Precision	1 mm (over 90% Area)	√	√	√	√	√	
Auto-Calibration	Yes	√	√	√	√	√	
Anti-light	Yes	√	√	√	√	√	
Minimum object size	2mm	√	√	√	√	√	
Touch Response Time	First Point <2 ms, Continuation <8 ms	√	√	√	√	√	
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√	√	√	√	√	
	Sound						
Front Speakers	15W*2 (20W*2 option)	√	√	√	√	√	
Subwoofer	20W*1 option	√	√	√	√	2.0 (2.1 option)	
Total Power Amplifiers	≦60w	√	√	√	√	√	
	Microphone (option	1)					
Туре	Wide-area microphones	√	√	√	√	√	
Number of Microphones	8	√	√	√	√	√	
Auto switch (Windows/Central)	Yes	√	√	√	√	√	
Disconnectable	Yes	√	√	√	√	√	
<u> </u>		·					
Number of images	4800M	√	√	√	√	√	
Maximum resolution and frame rate	4208*3120(30fps)	√	√	√	√	√	
FOV(field of view)	120 °	√	√	√	√	√	
	Front Side Connectio	ns					
Front Ports	Type-C * 1 line; I	HDMI IN * 3 line; USB3.0*2; USB	3-B*1				
Front Keys	Power on/off; Signal source; Setting; ECO; Menu; Volume down; Volume up						
NFC	, , , , , , , , , , , , , , , , , , ,						
Fingerprint		√					



Model		LT65RK3588	LT75RK3588	LT86RK3588	LT98RK3588	LT105RK3588
	Bottom Side Connection	ons				
Earphone	1	√	√	√	√	√
MIC IN	1	√	√	√	√	√
SPDIF OUT	1	√	√	√	√	√
RS232	1	√	√	√	√	√
Touch USB (USB B)	2	√	√	√	√	√
HDMI IN	1	√	√	√	√	√
HDMI OUT	1	√	√	√	√	√
RJ45	1	√	√	√	√	√
TYPE C OUT	1	√	√	√	√	√
Android USB2.0	1	√	√	√	√	√
Android USB3.0	1	√	√	√	√	√
TF CARD	1	√	√	√	√	√
WIFI	WIFI5+WIFI6+AP	√	√	√	√	√
Windows OPS Slot	80-pins OPS slot	√	√	√	√	√
Bluetooth version	5.2	V	V	V	√	V
	Riotouch Central		<u></u>			
Android Version	Android 13.0	√	√	√	√	√
Chip	Rockchip RK3588	√	√ V	√	√	√
CPU	quad-core Cortex-A76 and quad-core Cortex-A55, up to 2.4GHz	√	√	√	√	√
GPU	Mali-G610 MC4	√	√	√	√	√
RAM	8GB 16GB 32GB DDR4	√	√	√	√	√
Flash	128GB 256GB	√	√	V	√	√
Compliant with	Windows; Mac; Linux; Chrome OS	√ ·	V	V	V	√ V
Over-the-Air Updates (OTA)	YES	√ ·	V	V	V	√ V
Light Sensor	YES	V	V	V	V	√ V
NFC Reader/Writer	YES	· √	, , , , , , , , , , , , , , , , , , ,	, v	√ ×	V
Temperature, humidity and air quality three-in-one sensor	YES	√	√	√	√	√ ·
Fingerprint module	YES	√	V	V	√ ×	√
3-4	General Information					
Power Supply	~ 100-240 V (50/60Hz)	√	√ V	√	V	V
Switch On / Off	Yes	√	√	√	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√	√	V	V
Power Consumption		Maximun< 290W Eco<75W	Maximun< 320W Eco<75W	Maximun< 350W Eco<75W	Maximun< 510W Eco<75W	Maximun< 460W Eco<75W
Net Weight	(KG±2)	45	55	70	110	140
Gross Weight	(KG±2)	55	68	85	120	150
Screen Dimensions	(WxDxH)	1470.9 *97.5* 897.5 mm	1692.1 *97.5*1021.9 mm	1943.4*97.5*1166 mm	2250*97.5*12305mm	2505*97.5*1085mm
Dimensions Package	(WxDxH)	1622 * 190 * 1038mm	1842 * 190 * 1163 mm	2090 *190 * 1307 mm	2377*220*1486mm	2550*222*1120mm
VESA Standard	(mm)	600*400 mm	600*400 mm	800*600 mm	1195*220mm 630*47.5mm	
Certifications	CE: EMC + LVD / RoHS / REACH / FCC/CCC					
Warranty	ONE year for the whole product and THREE years for touch parts by default. (can be extended, it's for an option)	√	√	√	√	√
	Environmental condition	ons				
Operating Temperature	0°C - 40°C/32 - 100 °F	√	√	√	√	√
Storage Temperature	-20°C - 60°C/-4 - 140 °F	√	√	√	√	√
Storage Humidity	10 % - 90 %	√	√	√	√	√
Usage Humidity	10 % - 90 %	√	√	√	√	√
	Accessories					
Accessories	WIFI antenna*5pcs; No ink pen * 2pcs, Remote control *1pcs, 1.5m	power cord *1pcs, 1.5m HDMI	cable *1pcs, 1.5m USB touch co	able *1pcs; wall mount kit		



www.riotouch.com



+86 13631706431